



TECHNICAL DATA SHEET – Premium Acrylic Texture

An external premium full acrylic fine textured elastomeric coating for cement render, concrete and fibre cement sheets.

Features & Benefits

Conforms to AS4548.1-2 Long life coatings for masonry.
Excellent crack bridging and dirt resistance performance.
Easy to apply using a hawk and trowel onto primed substrates.
Available in a range of bright colours.
Non-toxic and cleans up with water.
10 Year Warranty when applied as a full Artex System.

Technical Parameters

80% Solids Content.
Coverage approx. 14sq.m/15L at a DFT of 1mm, depending on substrate type and conditions.
Apply between 10 – 35 degrees Celsius.
Do not apply if moisture is present in substrate and/or rain or wetting on the surface is imminent within full cure time.
15 minute join ability time under standard weather conditions.
Construction cure in 24 hours & full cure in 7 days.

Artex Premium Acrylic Texture is distributed and supplied by:

Artex Unit Trust - Unit 1 /32 Erceq Road Yangebup 6164 Contact 0419 196 153

Artex Premium Acrylic Texture TDS revised June 2016 by Artex Unit Trust

The data of this technical safety data sheet are current at the time of issue and relate only to the product and not to its use in combination with any other material or in any process. Artex Unit Trust disclaims responsibility for damages resulting from the use of or reliance upon the data of this material safety data sheet. No expressed or implied warranties are given other than those implied by Commonwealth, State or Territory legislation.
